

APPLICATION

FOR UNITED STATES LETTERS PATENT

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT I, **Henry E. Langeman**, a citizen of the United States,
have invented a new and useful guitar baffle system of which the following is a
specification:

1
2
3 **Guitar Baffle System**
4
5

6 **CROSS REFERENCE TO RELATED APPLICATIONS**

7 Not applicable to this application.
8
9

10 **STATEMENT REGARDING FEDERALLY**
11 **SPONSORED RESEARCH OR DEVELOPMENT**

12 Not applicable to this application.
13
14

15 **BACKGROUND OF THE INVENTION**
16
17
18

19 **Field of the Invention**
20

21 The present invention relates generally to acoustic guitars and more specifically
22 it relates to a guitar baffle system for increasing the volume of sound generated by a
23 guitar.
24
25

26 **Description of the Related Art**
27

28 Non-amplified guitars (e.g. acoustic guitars) have been in use for years. Figure
29 1 illustrates a conventional acoustic guitar comprised of a hollow guitar body (20) with

1 a sound hole (22) within a soundboard (28) wherein the soundboard is opposite of a
2 back wall (24), an elongate neck (23) extending from the guitar body, a bridge (21)
3 attached to the soundboard, and a plurality of guitar strings (25) attached between a
4 distal portion of the neck and to the bridge. When the strings vibrate, the vibrations
5 travel through the bridge to the soundboard thereby vibrating the soundboard. The body of
6 the guitar forms a hollow sound box that amplifies the vibrations of the soundboard. The
7 amplified sound travels through the sound hole within the soundboard.

8

9 While these devices may be suitable for the particular purpose to which they
10 address, they are not as suitable for increasing the volume of sound generated by a
11 guitar.

12

13

1

2 **BRIEF SUMMARY OF THE INVENTION**

3

4 In view of the foregoing disadvantages inherent in the known types of acoustic
5 guitars now present in the prior art, the present invention provides a new guitar baffle
6 system construction wherein the same can be utilized for increasing the volume of
7 sound generated by a guitar.

8

9 The general purpose of the present invention, which will be described
10 subsequently in greater detail, is to provide a new guitar baffle system that has many of
11 the advantages of the acoustic guitars mentioned heretofore and many novel features
12 that result in a new guitar baffle system which is not anticipated, rendered obvious,
13 suggested, or even implied by any of the prior art acoustic guitars, either alone or in
14 any combination thereof.

15

16 To attain this, the present invention generally comprises a baffle centrally
17 positioned within the guitar body. The baffle has a first end and a second end that are
18 distally spaced from the sidewall of the guitar body thereby forming a first opening and
19 a second opening respectively between thereof. The baffle is substantially parallel to a
20 soundboard of the guitar body. The baffle delays the sound amplified from the interior
21 of the guitar body.

22

23 There has thus been outlined, rather broadly, the more important features of the
24 invention in order that the detailed description thereof may be better understood, and
25 in order that the present contribution to the art may be better appreciated. There are
26 additional features of the invention that will be described hereinafter and that will form
27 the subject matter of the claims appended hereto.

28

29 In this respect, before explaining at least one embodiment of the invention in

1 detail, it is to be understood that the invention is not limited in its application to the
2 details of construction and to the arrangements of the components set forth in the
3 following description or illustrated in the drawings. The invention is capable of other
4 embodiments and of being practiced and carried out in various ways. Also, it is to be
5 understood that the phraseology and terminology employed herein are for the purpose
6 of the description and should not be regarded as limiting.

7
8 A primary object of the present invention is to provide a guitar baffle system
9 that will overcome the shortcomings of the prior art devices.

10
11 A second object is to provide a guitar baffle system for increasing the volume
12 of sound generated by a guitar.

13
14 Another object is to provide a guitar baffle system that may be utilized within
15 various types of acoustic guitars.

16
17 An additional object is to provide a guitar baffle system that is comprised of a
18 simple design.

19
20 A further object is to provide a guitar baffle system that has more sustain than a
21 conventional guitar.

22
23 Another object is to provide a guitar baffle system that delays the sound
24 coming from the backside of the guitar body.

25
26 Other objects and advantages of the present invention will become obvious to the
27 reader and it is intended that these objects and advantages are within the scope of the
28 present invention.

1 To the accomplishment of the above and related objects, this invention may be
2 embodied in the form illustrated in the accompanying drawings, attention being called
3 to the fact, however, that the drawings are illustrative only, and that changes may be
4 made in the specific construction illustrated and described within the scope of the
5 appended claims.

1
2 **BRIEF DESCRIPTION OF THE DRAWINGS**
3

4 Various other objects, features and attendant advantages of the present
5 invention will become fully appreciated as the same becomes better understood when
6 considered in conjunction with the accompanying drawings, in which like reference
7 characters designate the same or similar parts throughout the several views, and
8 wherein:
9

10 FIG. 1 is an upper perspective view of a conventional acoustic guitar.
11

12 FIG. 2 is an upper perspective view of the present invention.
13

14 FIG. 3 is an upper perspective view of a soundboard removed from the guitar
15 body.
16

17 FIG. 4 is an upper perspective view of a back wall removed from the guitar
18 body.
19

20 FIG. 5 is a front view of the present invention positioned within a guitar body.
21

22 FIG. 6 is a rear view of the present invention positioned within a guitar body.
23

24 FIG. 7 is a cross sectional view taken along line 7-7 of Figure 5.
25

26 FIG. 8 is a cross sectional view taken along line 8-8 of Figure 5.
27

DETAILED DESCRIPTION OF THE INVENTION

A. Overview

Turning now descriptively to the drawings, in which similar reference characters denote similar elements throughout the several views, FIGS. 1 through 8 illustrate a guitar baffle sytem 10, which comprises a baffle 30 centrally positioned within the guitar body 20. The baffle 30 has a first end 32 and a second end 34 that are distally spaced from the sidewall 26 of the guitar body 20 thereby forming a first opening 40 and a second opening 50 respectively between thereof. The baffle 30 is substantially parallel to a soundboard 28 of the guitar body 20. The baffle 30 delays the sound amplified from the interior of the guitar body 20.

B. Guitar Body

The present invention may be utilized in various types of guitar bodies and structures. Figures 1 through 8 illustrate an exemplary guitar body 20, however various other types of guitar bodies may be utilized within the present invention.

The guitar body 20 has an interior cavity that assists in amplifying the sound. The guitar body 20 typically comprises a soundboard 28 having a sound hole 22, at least one sidewall 26 attached to the soundboard 28, a bridge 21 attached to the sound board, a back wall 24 attached to the sidewall 26 opposite of the soundboard 28, and a neck 23 extending from the guitar body 20 as illustrated in Figures 1 through 8 of the drawings. Various other conventional acoustic and non-acoustic guitar components may be attached to the guitar body 20 as can be appreciated.

C. Baffle

The baffle 30 attached to the sidewall 26 within the interior cavity of the guitar body 20 substantially parallel to the soundboard 28. As shown in Figure 7 of the

1 drawings, the baffle 30 is attached to opposing interior surfaces of the sidewall 26.
2 The baffle 30 separates the interior cavity of the guitar body 20 into an upper cavity 27
3 and a lower cavity 29. The baffle 30 may have a flat and straight structure as
4 illustrated in Figures 3, 4, 7 and 8 of the drawings.

5
6 The baffle 30 may be positioned centrally between the back wall 24 and the
7 soundboard 28 as illustrated in Figures 3, 4, 7 and 8 of the drawings. A first opening
8 40 is between the sidewall 26 and a first end 32 of the baffle 30 as shown in Figures 3
9 and 4 of the drawings.

10
11 A second opening 50 is between the sidewall 26 and a second end 34 of the
12 baffle 30 as further shown in Figures 3 and 4 of the drawings. The first opening 40
13 and the second opening 50 fluidly connect the upper cavity 27 and the lower cavity 29
14 to allow sound waves to travel between thereof.

15
16 The second end 34 of the baffle 30 may be straight as shown in Figures 3 and 4
17 of the drawings. The second end 34 may be substantially transverse with respect to a
18 longitudinal axis of the guitar body 20 as further shown in Figures 3 and 4 of the
19 drawings. The second end 34 of the baffle 30 is positioned near an end of the guitar
20 body 20 opposite of the neck 23 as shown in Figure 4 of the drawings.

21
22 The first end 32 of the baffle 30 has a center cutout corresponding to the sound
23 hole 22 as shown in Figure 4 of the drawings. The first end 32 of the baffle 30 has two
24 opposing slanted side portions as shown in Figures 3 and 4 of the drawings.

25 26 ***D. Operation of Invention***

27 In use, when the strings 25 of the guitar are struck by a user, the vibrations of
28 the strings 25 are transferred to the bridge 21 and then to the soundboard 28. The
29 soundboard 28 vibrates accordingly and generates sound waves within the interior

1 cavity of the guitar body 20. The baffle 30 also vibrates according to the sound waves
2 and assists in amplifying the sound before being emitted through the sound hole 22.
3 The baffle 30 also delays the sound reflected from the back wall 24 and the lower
4 cavity 29 thereby creating a sustained sound from the guitar. In addition, the first
5 opening 40 and the second opening 50 act as dual air columns reinforcing each other as
6 the baffle 30 vibrates according to the sound waves.

7
8 As to a further discussion of the manner of usage and operation of the present
9 invention, the same should be apparent from the above description. Accordingly, no
10 further discussion relating to the manner of usage and operation will be provided.

11
12 With respect to the above description then, it is to be realized that the optimum
13 dimensional relationships for the parts of the invention, to include variations in size,
14 materials, shape, form, function and manner of operation, assembly and use, are
15 deemed to be within the expertise of those skilled in the art, and all equivalent
16 structural variations and relationships to those illustrated in the drawings and
17 described in the specification are intended to be encompassed by the present invention.

18
19 Therefore, the foregoing is considered as illustrative only of the principles of
20 the invention. Further, since numerous modifications and changes will readily occur to
21 those skilled in the art, it is not desired to limit the invention to the exact construction
22 and operation shown and described, and accordingly, all suitable modifications and
23 equivalents may be resorted to, falling within the scope of the invention.